GIS Based Traffic Safety Analysis for Identification of High Collision Locations in the City of Regina Road Network

Asma Chowdhury

Environmental Systems Engineering, University of Regina

Kwei Quaye, PhD, PEng.

Traffic Safety and Driver Services, Saskatchewan Government Insurance





INTRODUCTION

- Regina, the capital city of Saskatchewan, is the eighteenth largest city of Canada by population. The city is the fourth fastest growing census metropolitan area in Canada.
- A total of 30,173 collisions were reported across the province of Saskatchewan by the Traffic Accident Information System of Saskatchewan Government Insurance (SGI) in 2012. Regina recorded 4,586 collisions, 1,558 injuries and 7 deaths in 2012 (TAIS Annual Report, 2013).
- In 2013, the overall collision numbers in province increased to 31,734 and Regina recorded 5,786 collisions, 1,405 injuries and 8 deaths in 2013 (TAIS Annual Report, 2014).

RESEARCH OBJECTIVE

- There is a need to understand where, when and how traffic collisions occurred to improve road safety and reduce traffic accidents in the City of Regina road network.
- By knowing where and when traffic accidents usually occur, traffic safety measures could be taken in an improved manner.
- Therefore, the objective of this study was to identify high collision road locations for the city of Regina road network using GIS and spatial data analysis.






DATA COLLECTION AND PROCESSING


- This study used eight years of collision data (1998–2006) for the City of Regina. Two different databases and a traffic volume map were used for this project.
- A roadway network base map for the City of Regina (ArcGIS shapefile format) was collected from TerraServer of The Environmental Research and Response Applications (TERRA) Laboratory, University of Regina.
- A Geodatabase of collision history (1998–2006) for the City of Regina was collected from the Traffic Accident Information System (TAIS) of Saskatchewan Government Insurance (SGI).
- The annual traffic flow map was collected from the City of Regina to select high traffic volume roads in the city network.
- This research illustrates the application of GIS methods to accident analysis so the data being used is a bit dated (i.e., 1998-2006)


RESEARCH METHODOLOGY

- The analysis of this study was divided into two major sections.
- In the first section, initially the Spatial Analyst tools were used to identify the hot zones in the entire city for fatal collisions only, fatal and injury collisions, and total collisions.
- Subsequently, Spatial Statistics tools were used in conjunction with Kernel Density Estimation (KDE) to identify statistically significant hot spots and cold spots. KDE analysis was also conducted for day and night time collisions for the entire city.
- In the second section, the top twenty roads were selected from the city road network based on the traffic volume and the required data was reclassified accordingly.
- Finally, KDE was used to identify intersection of high collision occurrence on these selected roadways.

HISTORICAL TREND OF TRAFFIC ACCIDENTS









Top 20 High Traffic Volume Roads in City Road Network


Selected top 20 roads with high traffic volume roads in the City network by City of Regina's Traffic flow map




KERNEL DENSITY AND POINT DENSITY ANALYSIS




Hot Spots and Kernel density for the City of Regina






Day Time Collision density Map of the City of Regina



Night Time Collision density Map of the City of Regina



SUMMARY AND CONCLUSIONS

- The downtown area of the city has been classified as the hot zone of Regina by the both tools. Another hot zone was detected for fatal collisions only in the northeast neighbourhood of the city.
- Hot Spot Analysis, a Spatial Statistics tool, was used for identifying statistically significant hot and cold spots. The resultant map was compared with an analysis conducted by the Kernel density tool for the entire road network.
- Almost all hot spots were found to be located in the downtown area, which was similarly classified as a hot zone from the analysis with the Kernel density tool.

SUMMARY AND CONCLUSIONS

- The downtown area was found as a hot zone during the day time whereas two additional zones were observed as hot zones, while still including the downtown area for night time. These two additional zones are located on Dewdney east -Arcola neighbourhood and Whitmore - Albert park neighbourhood.
- The analysis identified over 30 hot spots in different roadways of the city network. The intersection at Albert Street and Saskatchewan Drive was ranked as the top hot spot.
- Most of the hot spots are found to be located within and nearby of the downtown area on different roadways. It was observed that the hot spots are primarily located in two major roadways: Albert Street which runs north/south; Victoria Avenue which runs east/west.

SUMMARY AND CONCLUSIONS

- In the east area of the city, the intersections of Arcola Avenue
 University park Drive and Princes of Wales Drive Victoria Avenue were identified as hot spots.
- The intersection of Albert Street Parliament Avenue, in the south area of the city, was identified as hot spots.
- All hot spots are located on the Lewvan Drive in the west part of the city. Intersection at McCarthy and Rochdale Boulevard is the major point of high collision occurrence in the city of Regina's Northwest area.
- There are three intersections equipped for red light cameras in the city of Regina's road network since 1999. All of these 3 intersections were also detected as hot spots on this study.

RECOMMENDATIONS AND PATH FORWARD

- This GIS based analysis provided hot zones for the entire city and also identified hot zones on different time scales. Therefore, it gives a baseline for traffic safety units of the Regina Police Services to easily develop plans for community programs and their traffic enforcement services.
- The research outcomes can also be applied for policy and analytical purpose to Red Light Camera and peed Enforcement Programs in the City of Regina road networks.
- This approach could be extended to other types of crash data analysis (e.g. time of occurrence, major contributing factors, environmental factors, and driver factors etc.).

ACKNOWLEDGEMENTS

- SGI Traffic Accident Information System (TAIS).
- Dr. Joseph Piwowar and Ms. Jessica Vanstone, Department of Geography and Environmental Studies, University of Regina.
- The Environmental Research and Response Applications (TERRA) Laboratory, University of Regina.
- Faculty of Engineering and Applied Science, University of Regina.
- Faculty of Graduate Studies and Research, University of Regina.

DISCLAIMER

Any views or interpretation of data analysis presented in this work are solely those of the authors. SGI is not responsible for the interpretation of the data and accepts no liability for the content of this work.